



M12 5-PIN FEMALE
CAN BUS

M12 4-PIN MALE
POWER



Detail A



CAN BUS			
PIN	FUNCTION	SPECIFICATION	WIRE CLR
1	NC	-	
2	NC	-	RD
3	NC	-	BK
4	CAN H	1MBaud Max (non-isolated)	WH
5	CAN L	1MBaud Max (non-isolated)	BU

POWER			
PIN	FUNCTION	SPECIFICATION	WIRE CLR
1	MAIN POWER	+20-48 VDC	BN
2	CONTROL POWER	+20-48 VDC (DE-Option)	WH
3	GND-MAIN-PWR	Ground Main Power	BU
4	GND-CNTRL-PWR	Ground Control Power	BK

Allgemeintol. nach ISO 2768-mK Standard toler. acc. ISO 2768-mK				A3	Moog Memmingen GmbH / Germany / www.moog-memmingen.com				Ersatz für / Replace for:		
					- DATUM DATE	NAME NAME	MAßSTAB SCALE	FARBE / OBERFLÄCHE COLOR / SURFACE	MOOG		
					Gez. Draw	17.05.2016	A. Schlegel	2:3			
					Zul. Last cha	21.11.2019	K. Umeri				
					MATERIAL / MATERIAL:						
ÄNDERUNG CHANGE	VERS. VERS	DATUM DATE	NAME NAME	BENENNUNG / TITLE							
Erstfassung / Initial Drawing	1	17.05.2016	A. Schlegel	SM23165x-BRK-C (SM23165S-BRK-C AND SM23165ST-BRK-C SERIES)							
Connector Changes: 5-Pin_CAN / 4-Pin_POWER	2	13.07.2017	A. Schlegel								
Part number changed	3	09.01.2018	A. Schlegel								
Title changed & Inch dimensions added	4	19.11.2019	K. Umeri	ARTIKEL-NR. / ARTICLE-NR.:					BLATT SHEET		
									1/1		
									VERSION VERSIO		
									04		